

JVS-N915-BDL

3.0MP Full-Color PoE Network Camera



Features

- 3MP HD resolution
- The default is smart dual light, the lights turn on when human detected and turn off when no human detected
- Built-in Mic
- Built-in PoE
- IP67

Specifications

Video	
Image Sensor	1/2.9" CMOS Sensor
Max Resolution	2304x1296
Effective Pixels	3.0MP
Compression Standard	H.264/H.265
Framerate	20fps
Bitrate	Main Stream: 128Kbps ~ 4Mbps Sub Stream: 68Kbps~1024Kbps
SNR (dB)	50dB
Min. Illumination	0Lux (light ON)
Lens	
Interface Type	M12
Lens	4mm, 6mm
FOV	4mm:H 80.9° , V 44.06° , D 94.7° 6mm:H 53.8° , V 28.9° , D 61.4°
Function	
Audio Codec	G.711U/G.711A (default)
Exposure Control	Auto
OSD Information Setting	Large font OSD, OSD flashing on alarm, OSD position settings
Schedule Reboot	Support
Smart Defog	Support
Motion Detection	Support (Humanoid)
Image Setting	Support Saturation, Brightness, Contrast adjustment
Image Style	Standard, Soft, Transparent
Day and Night Function	Auto IR, smart dual light.
Privacy Mask	Support up 8 areas

Electronic Screen Setting	Support maximum and minimum exposure time setting
DWDR	Support
Screen Settings	Screen mirroring, Screen flipping
IP Adaptation	Support automatic adaptation of IP address (Optional)
Alarm Method	Email Alarm, Client Alarm
Remote Operation	System, Audio and Video, Image, Alarm, Network management
Audio Function	Built-in Mic
Network	
Ethernet	10/100Mbps Ethernet
Stream	2x Streams
Network Protocols	HTTP, TCP/IP, UDP, RTSP, DHCP, DNS
ONVIF	Standard ONVIF
Network Transmission	CloudSEE 2.0
Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
User	Up to 13 Users
App	Support iOS/Android
General	
Lights	4 White LEDs + 4 IR LEDs
IR Distance	Up to 40 Meters
Waterproof Level	IP67
Power Supply	DC12V 2A or PoE
Power Consumption	<3W (During Day); <6W (At Night)
Working Temperature	-20°C ~ 60°C
Working Humidity	<93% Rh
Color/Material	Black and White/ Plastic + Metal
Dimensions (WxHxD)	88x85x178mm
Weight	240g
Installation Method	Wall or ceiling mount