

JVS-XD2516-FC10T

16CH 5MN XVR



Key Features

- TVI / AHD / DVR / NVR / CVI 5-in-1 function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.
- Supports various mobile phone monitoring (iPhone Android).
- Support multiple web browsers (IE / Chrome / Firefox / Safari).
- Support VGA,HDMI output at the same time.
- Support STVI function(Need camera support STVI).
- Support coaxial audio
- Support multi-languauge

Description



① ALARM ② REC ③ POWER ① ② ③



| Index | Description | Index | Description |
|-------|-------------|-------|-------------|
| ① | Video In | ⑥ | RJ45 |
| ② | Video Out | ⑦ | USB |
| ③ | HDMI | ⑧ | Power |
| ④ | Audio In | ⑨ | VGA |
| ⑤ | Audio Out | | |

Specifications

| Model | JVS-XD2516-FC10T |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| System | |
| Compression | H.265 |
| O/S | Embedded Linux O/S |
| Video and Audio | |
| Video Input | 16CH,BNC |
| Preview Ability | 16*5MN@12.5fps (4 in 1) (support 12.5fps when camera is 5MP) 16*4MN@15fps (4 in 1) (support 15fps when camera is 4MP) 16*1080N@25fps (4 in 1) |
| Coding Ability | 16*5MN@6fps (4 in 1) 16*4MN@8fps (4 in 1) 16*1080N@15fps (4 in 1) |
| Decoding Ability | 16*5MN@6fps (4 in 1) 16*4MN@8fps (4 in 1) 16*1080N@15fps (4 in 1) |
| Video Output | 1CH VGA;1CH HDMI |
| Channel Mode | Support any channel mode combination (5MN analog + 1080P digital) |
| Audio In & Out | 1/1, RCA |
| Video Standard | PAL/NTSC |
| Storage | |
| SATA | 1x SATA Interface |
| Capacity | Up to 8TB Max. |
| File Format | H.265 |
| Backup Mode | USB |
| Playback and Backup | |
| Video Playback | Auto/Timing/ Motion Detection |
| Sync Playback | 16CH |
| Search Mode | Point-in-time search, Calendar search, Event search, Channel search |
| Network | |
| Ethernet | 10 / 100 Mbps,1 RJ45 |
| Network Function | TCP/IP, DHCP, DDNS, NTP, SMTP |
| Interoperability | ONVIF Standard |
| Smart Phone | iPhone, Android |
| Hardware | |
| Network Interface | 1x RJ45 |
| USB Interface | 2x USB2.0 |
| Controlling Device | Mouse |
| Alarm Input | Not Support |
| Alarm Output | Not Support |
| Special | |
| Multi-Screen Display | 1/4/8/9/16 |
| Alarm Method | Email Alarm |
| Digital Zoom | Not Support |
| Two-Way Talk | Support |
| Alarm Snapshot | Support |
| Intelligent Analysis | Support Motion Detection、Video Tampering、Video loss |
| General | |
| Power Supply | DC12V/2A |
| Consumption | ≤8W (without HDD) |
| Working Temperature | -10°C ~60°C |
| Working Humidity | 10% ~ 90% Humidity |
| Dimensions | 250x223x42mm |
| Weight | 837g |