

JVS-XD2608-FC10V

8CH 5M-N 5-in-1 XVR



Key Features

- TVI / AHD / CVBS / CVI / IP 5-in-1 Function, Multi-mode Input, Support HD Analog Video Encoding, Support HD Analog + HD Network Video Input, Support Pure HD Network Video Input.
- Support Various Mobile Phone Monitoring (iPhone Android).
- Support VGA,HDMI Output At The Same Time.
- Support Coaxial Audio



Index	Description	Index	Description
①	Video In	⑥	RJ45
②	Video Out	⑦	USB
③	HDMI	⑧	Power
④	Audio In	⑨	VGA
⑤	Audio Out		

Specifications

System

Compression	H.265
O/S	Embedded Linux O/S

Video and Audio

Video Input	8CH BNC+4CH IPC
Preview Ability	8*5MN@12.5fps (4 in 1) 8*4MN@12.5fps (4 in 1) 8*1080N@25fps (4 in 1)
Coding Ability	8*5MN@6fps (4 in 1) 8*4MN@8fps (4 in 1) 8*1080N@15fps (4 in 1)
Decoding Ability	8*5MN@6fps (4 in 1) 8*4MN@8fps (4 in 1) 8*1080N@15fps (4 in 1)
Video Output	1CH VGA;1CH HDMI
Channel Mode	Support any channel mode combination (5MN analog + 5M digital)
Audio In & Out	1/1, RCA 8CH coaxial audio input + 4 channels network audio
Video Standard	PAL/NTSC

Storage

SATA	1x SATA Interface
Capacity	Up to 8TB Max.
Backup Mode	USB

Playback and Backup

Video Playback	Auto/Timing/ Motion detection
Sync Playback	4CH
Search Mode	Point-in-time search, calendar search, event search, channel search

Network

Ethernet	10 / 100 Mbps,1 RJ45
Network Function	TCP/IP, DHCP, DDNS, NTP, SMTP
Interoperability	ONVIF Standard
Smart Phone	iPhone, Android

Hardware

Network Interface	1x RJ45
USB Interface	2x USB2.0
PTZ Interface	Not Support
Controlling Device	Mouse
Alarm Input	Not Support
Alarm Output	Not Support

Special

Multi-Screen Display	1,4,5,6,7,8, 9,10, 12
Alarm Method	Email Alarm
Digital Zoom	Support
Two-Way Talk	Not Support
Alarm Snapshot	Support
Intelligent Analysis	Support Motion Detection

General

Power Supply	DC12V /2A
Consumption	≤ 15 W
Working Temperature	-10 ° C ~55 ° C
Working Humidity	10% ~ 90% Humidity
Dimensions	250x223x42mm
Weight	830g