

JVS-XD2716-FC10T

16CH 1080N 5-in-1 XVR



Key Features

- TVI / AHD / DVR / NVR / CVI five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.
- Easily implement network penetration through cloud services and remote monitoring in one step.
- Supports various mobile phone monitoring (iPhone Android).
- Support multiple web browsers (IE / Chrome / Firefox / Safari).
- Support VGA, HDMI output at the same time.
- Supports more than 20 languages and breaks the limits of national borders.
- Freely change the startup interface and choose the interface style.
- Support humanoid functions.
- Support STVI function.
- Support coaxial audio.
- Support CloudSEE.



① ALARM ② REC ③ POWER ① ② ③



| Index | Description | Index | Description |
|-------|-------------|-------|-------------|
| ① | Video In | ⑥ | RJ45 |
| ② | Video Out | ⑦ | USB |
| ③ | HDMI | ⑧ | Power |
| ④ | Audio In | ⑨ | VGA |
| ⑤ | Audio Out | | |

Specifications

System

| | |
|-------------|--------------------|
| Compression | H.265 |
| O/S | Embedded Linux O/S |

Video and Audio

| | |
|------------------|---|
| Video Input | 16CH,BNC |
| Preview Ability | 16*1080N/25fps |
| Coding Ability | 16*1080N/15fps |
| Decoding Ability | 16*1080N/15fps |
| Video Output | 1CH VGA;1CH HDMI |
| Channel Mode | Support any channel mode combination (1080N analog + 1080P digital) |
| Audio In & Out | 1/1, RCA |
| Coaxial Audio | 16 |
| Two-way Intercom | Support |

Storage

| | |
|-------------|-------------------|
| SATA | 1x SATA Interface |
| File Format | H.26X、AVI |
| Backup Mode | USB |

Playback and Backup

| | |
|----------------|---|
| Video Playback | Auto/Timing/ Motion detection |
| Sync Playback | 16CH |
| Search Mode | Point-in-time search, calendar search, event search, channel search |

Network

| | |
|------------------|-------------------------------|
| Ethernet | 10 / 100 Mbps,1 RJ45 |
| Network Function | TCP/IP, DHCP, DDNS, NTP, SMTP |
| Interoperability | ONVIF Standard |
| Smart Phone | iPhone, Android |

Hardware

| | |
|--------------------|-------------|
| Network Interface | 1x RJ45 |
| Controlling Device | Mouse |
| Alarm Input | Not Support |
| Alarm Output | Not Support |

General

| | |
|---------------------|--------------------|
| Power Supply | DC12V /2A |
| Working Temperature | -10° C ~60° C |
| Working Humidity | 10% ~ 90% Humidity |